

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
 Article number : 64104
 Product code : 641

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Function or use category : Paint

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

BARDAHL NL - OCD NEDERLAND BV
 Maxwellstraat 41
 3316 GP Dordrecht - Nederland
 T 0031 78 651 2322 - F 0031 78 617 4848
rjonker@bardahl.nl - www.bardahl.nl

1.4. Emergency telephone number

Emergency number : +31 (0) 6 2908 2010
 During office hours: 8.30 t/m 17:00 h

Country	Official advisory body	Address	Emergency number	Comment
Ireland	National Poisons Information Centre Beaumont Hospital	PO Box 1297 Beaumont Road 9 Dublin	+353 1 809 2566 +353 1 809 2166 (public, 8am - 10pm, 7/7)	

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Aerosol, Category 1 H222;H229
 Serious eye damage/eye irritation, Category 2 H319
 Specific target organ toxicity — Single exposure, Category 3, Narcosis H336

Full text of H statements : see section 16

Adverse physicochemical, human health and environmental effects

Inhalation of fumes or vapours may cause respiratory irritation. May irritate eyes and skin. May cause headache, nausea and irritation of respiratory tract. The preparation is not classified as "dangerous for the environment.". Can form explosive mixture with air. Exposure to fire may cause containers to rupture/explode.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS02

GHS07

Signal word (CLP) : Danger
 Hazard statements (CLP) : H222 - Extremely flammable aerosol
 H319 - Causes serious eye irritation
 H336 - May cause drowsiness or dizziness
 Precautionary statements (CLP) : P102 - Keep out of reach of children
 P271 - Use only outdoors or in a well-ventilated area

Racing Black

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

P280 - Wear protective gloves, protective clothing, face protection
 P261 - Avoid breathing vapours, spray
 P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
 P337+P313 - If eye irritation persists: Get medical advice/attention
 P501 - Dispose of contents/container in accordance with local regulations
 P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
 P211 - Do not spray on an open flame or other ignition source
 P251 - Pressurized container: Do not pierce or burn, even after use
 P264 - Wash hands, forearms and face thoroughly after handling
 P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing
 P312 - Call a POISON CENTER or doctor/physician if you feel unwell
 P403+P233 - Store in a well-ventilated place. Keep container tightly closed
 P405 - Store locked up
 P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

EUH-statements : EUH066 - Repeated exposure may cause skin dryness or cracking

2.3. Other hazards

vPvB: not relevant – no registration required

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
acetone, propan-2-one, propanone	(CAS No) 67-64-1 (EC no) 200-662-2 (EC index no) 606-001-00-8 (REACH-no) 01-2119471330-49	30 - 60	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
Butane	(CAS No) 106-97-8 (EC no) 203-448-7 (REACH-no) 01-2119474691-32	10 - 30	Flam. Gas 1, H220 Compressed gas, H280
propane (Note U)	(CAS No) 74-98-6 (EC no) 200-827-9 (REACH-no) 01-2119486944-21	10 - 30	Flam. Gas 1, H220 Compressed gas, H280
Isobutane	(CAS No) 75-28-5 (EC no) 200-857-2 (REACH-no) 01-2119485395-27	5 - 10	Flam. Gas 1, H220 Compressed gas, H280
xylene (Note C)	(CAS No) 1330-20-7 (EC no) 215-535-7 (EC index no) 601-022-00-9 (REACH-no) 01-2119488216-32	5 - 10	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 STOT RE 2, H373 Asp. Tox. 1, H304
1-methoxy-2-propanol, monopropylene glycol methyl ether	(CAS No) 107-98-2 (EC no) 203-539-1 (REACH-no) 01-2119457435-35	1 - 5	Flam. Liq. 3, H226 STOT SE 3, H336
2-butoxyethanol, ethylene glycol monobutyl ether, butyl cellosolve	(CAS No) 111-76-2 (EC no) 203-905-0 (EC index no) 603-014-00-0 (REACH-no) 01-2119475108-36	1 - 5	Acute Tox. 4 (Inhalation), H332 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Oral), H302 Eye Irrit. 2, H319 Skin Irrit. 2, H315
1,2,4-trimethylbenzene	(CAS No) 95-63-6 (EC no) 202-436-9 (EC index no) 601-043-00-3 (REACH-no) 01-2119472135-42	< 1	Flam. Liq. 3, H226 Acute Tox. 4 (Inhalation), H332 Eye Irrit. 2, H319 STOT SE 3, H335 Skin Irrit. 2, H315 Aquatic Chronic 2, H411
mesitylene, 1,3,5-trimethylbenzene	(CAS No) 108-67-8 (EC no) 203-604-4 (EC index no) 601-025-00-5	< 1	Flam. Liq. 3, H226 STOT SE 3, H335 Aquatic Chronic 2, H411

Specific concentration limits:

Name	Product identifier	Specific concentration limits
mesitylene, 1,3,5-trimethylbenzene	(CAS No) 108-67-8 (EC no) 203-604-4 (EC index no) 601-025-00-5	(C >= 25) STOT SE 3, H335

Racing Black

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Note C : Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.

Note U : When put on the market gases have to be classified as 'Gases under pressure', in one of the groups compressed gas, liquefied gas, refrigerated liquefied gas or dissolved gas. The group depends on the physical state in which the gas is packaged and therefore has to be assigned case by case.

Full text of H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Assure fresh air breathing. Seek medical attention if ill effect develops.
First-aid measures after inhalation	: Allow breathing of fresh air. If breathing is irregular or stopped, administer artificial respiration. Keep the victim warm. Allow the victim to rest. Obtain emergency medical attention.
First-aid measures after skin contact	: Wash skin thoroughly with mild soap and water. If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after eye contact	: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 15 minutes, holding the eyelids apart. Seek medical attention if irritation develops.
First-aid measures after ingestion	: Do NOT induce vomiting. Drink plenty of water. Never give anything by mouth to an unconscious person. If swallowed, rinse mouth with water (only if the person is conscious). Seek medical attention if ill effect develops.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries after inhalation	: Exposition on high concentrations can cause : May cause headache, nausea and irritation of respiratory tract. This material or its emissions may affect the central nervous system and/or aggravate pre-existing disorders.
Symptoms/injuries after skin contact	: Effects of skin contact may include : redness. Skin irritation.
Symptoms/injuries after eye contact	: Irritating to eyes. Redness, pain.
Symptoms/injuries after ingestion	: Ingestion unlikely.

4.3. Indication of any immediate medical attention and special treatment needed

No specific first aid measures are required.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Powder. Dry chemical. Sand. Dolomite. Water spray. Water haze.

5.2. Special hazards arising from the substance or mixture

Fire hazard	: High temperature may liberate toxic gases.
Explosion hazard	: Heating may cause an explosion.

5.3. Advice for firefighters

Firefighting instructions	: Use water spray or fog for cooling exposed containers.
Protection during firefighting	: Wear suitable protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Remove ignition sources. No open flames. No smoking. Do not breathe gas, fumes, vapour or spray. Avoid contact with skin and eyes.

6.1.1. For non-emergency personnel

No additional information available

6.1.2. For emergency responders

Protective equipment : Wear proper protective equipment.

6.2. Environmental precautions

Not relevant.

6.3. Methods and material for containment and cleaning up

Other information : Wear suitable protective clothing. Eliminate every possible source of ignition. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ventilate area. Clear all other personnel from the area.

6.4. Reference to other sections

See Heading 8. See Heading 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Avoid contact with skin and eyes. Do not breathe gas, fumes, vapour or spray.

Racing Black

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Precautions for safe handling : Ensure all national/local regulations are observed. Wear suitable respiratory equipment.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Do not expose to temperatures exceeding 50 °C/ 122 °F. Store in dry, cool, well-ventilated area.

Incompatible materials : heat. sparks. Open flame. Direct sunlight. Moisture.

7.3. Specific end use(s)

Aerosolized paint spray.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

1,2,4-trimethylbenzene (95-63-6)		
EU	IOELV TWA (mg/m ³)	125 mg/m ³
EU	IOELV TWA (ppm)	25 ppm
1-methoxy-2-propanol, monopropylene glycol methyl ether (107-98-2)		
EU	Local name	1-Methoxypropanol-2
EU	IOELV TWA (mg/m ³)	375 mg/m ³
EU	IOELV TWA (ppm)	100 ppm
EU	IOELV STEL (mg/m ³)	568 mg/m ³
EU	IOELV STEL (ppm)	150 ppm
EU	Notes	Skin
acetone, propan-2-one, propanone (67-64-1)		
EU	Local name	Acetone
EU	IOELV TWA (mg/m ³)	1210 mg/m ³
EU	IOELV TWA (ppm)	500 ppm
mesitylene, 1,3,5-trimethylbenzene (108-67-8)		
EU	IOELV TWA (mg/m ³)	125 mg/m ³
EU	IOELV TWA (ppm)	25 ppm
propane (74-98-6)		
EU	IOELV TWA (ppm)	1000 ppm
Netherlands	Suffocating	
xylene (1330-20-7)		
EU	IOELV TWA (mg/m ³)	435 mg/m ³
EU	IOELV TWA (ppm)	100 ppm
EU	IOELV STEL (ppm)	150 ppm

8.2. Exposure controls

Personal protective equipment : Gloves. Protective goggles.

Hand protection : Safety gloves

Eye protection : Safety glasses with side guards should be worn to prevent injury from airborne particles and/or other eye contact with this product

Skin and body protection : Wear suitable protective clothing

Respiratory protection : In case of insufficient ventilation, wear suitable respiratory equipment. Use protection with appropriate chemical pattern



Other information : No smoking. Good ventilation of the workplace required. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Do not eat, drink or smoke during use. Remove contaminated clothing immediately.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid

Appearance : Aerosol.

Racing Black

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Colour	: Black.
Odour	: characteristic.
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: The resin binder in the paint film begins to soften at temperatures in excess of 60 degrees celsius.
Freezing point	: No data available
Boiling point	: The boiling point of the lowest boiling point material is minus 104 degrees celcius (-104). This is the boiling point of the propellant (LPG - Liquefied Petroleum Gas).
Flash point	: The flash point of the lowest flash point material is minus 104 degrees celcius (-104). This is the flash point of the propellant (LPG - Liquefied Petroleum Gas).
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapour pressure	: 590 - 1760 kPa
Relative vapour density at 20 °C	: >1 (Heavier than air)
Relative density	: < 1 Ambient
Solubility	: Insoluble in water.
Log Pow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: 0.8 - 13 vol %

9.2. Other information

VOC content	: 656 g/l Aerosol products which are used for vehicle refinishing are classed as Annex IIB subcategory (e). The maximum permitted VOC's are 840 g/l. The typical VOC content for this range of products is between 625 and 675 g/l. The VOC regulations do not apply to any other aerosol products except those which are used for vehicle refinishing.
-------------	---

SECTION 10: Stability and reactivity

10.1. Reactivity

In use may form flammable/explosive vapour-air mixture.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No additional information available

10.4. Conditions to avoid

Heat. Open flame. Sources of ignition. Direct sunlight.

10.5. Incompatible materials

Strong oxidizers. Strong bases. Strong acids.

10.6. Hazardous decomposition products

Carbon dioxide. Carbon monoxide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : May cause stomach cramps and vomiting. May cause gastric irritation

1-methoxy-2-propanol, monopropylene glycol methyl ether (107-98-2)	
LD50 oral rat	5660 mg/kg
LD50 dermal rabbit	13000 mg/kg
LC50 inhalation rat (mg/l)	6 mg/l/4h

2-butoxyethanol, ethylene glycol monobutyl ether, butyl cellosolve (111-76-2)	
LD50 oral rat	1480 mg/kg
LD50 dermal rabbit	400 mg/kg

Racing Black

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

acetone, propan-2-one, propanone (67-64-1)	
LD50 oral rat	5800 mg/kg
LD50 dermal rabbit	7800 mg/kg
LC50 inhalation rat (mg/l)	> 20 mg/l/4h
Butane (106-97-8)	
LC50 inhalation rat (mg/l)	658 mg/l/4h
Isobutane (75-28-5)	
LC50 inhalation rat (mg/l)	> 50 mg/l/4h
propane (74-98-6)	
LC50 inhalation rat (mg/l)	20 mg/l/4h
xylene (1330-20-7)	
LD50 oral rat	4300 mg/kg
LD50 dermal rabbit	2000 mg/kg
LC50 inhalation rat (mg/l)	6350 mg/l/4h

Skin corrosion/irritation	: Prolonged or repeated contact may cause skin to become dry or cracked. May degrease the skin. Irritating to skin. Eczema
Serious eye damage/irritation	: Irritating to eyes. May cause chemical eye burns
Respiratory or skin sensitisation	: May cause respiratory irritation. Vapours may cause drowsiness and dizziness. Headache
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
Specific target organ toxicity (single exposure)	: May cause drowsiness or dizziness.
Specific target organ toxicity (repeated exposure)	: Not classified
Aspiration hazard	: Not classified

SECTION 12: Ecological information

12.1. Toxicity

acetone, propan-2-one, propanone (67-64-1)	
EC50 Daphnia 1	8800 mg/l
Butane (106-97-8)	
LC50 fish 1	680 mg/l (96h)
xylene (1330-20-7)	
LC50 other aquatic organisms 1	8.9 - 16.4 mg/l (Pimephales promelas 96h)
EC50 Daphnia 1	3.2 - 9.5 mg/l (Daphnia magna) (48h)

12.2. Persistence and degradability

64104	
Persistence and degradability	This material is expected to be readily biodegradable.
Butane (106-97-8)	
Persistence and degradability	Readily biodegradable.
Isobutane (75-28-5)	
Persistence and degradability	Readily biodegradable.
propane (74-98-6)	
Persistence and degradability	Readily biodegradable.
xylene (1330-20-7)	
Persistence and degradability	Readily biodegradable.

12.3. Bioaccumulative potential

64104	
Bioaccumulative potential	Bioaccumulation potential.
xylene (1330-20-7)	
BCF fish 2	7 - 26
Bioconcentration factor (BCF REACH)	< 500
Log Pow	3.2

Racing Black

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

12.4. Mobility in soil

64104

Ecology - soil

The product contains volatile organic compounds (VOC) which will evaporate easily from all surfaces.

Butane (106-97-8)

Ecology - soil

If released into the environment, the product will rapidly disperse into the atmosphere where it will undergo photochemical degradation.

Isobutane (75-28-5)

Ecology - soil

If released into the environment, the product will rapidly disperse into the atmosphere where it will undergo photochemical degradation.

propane (74-98-6)

Ecology - soil

If released into the environment, the product will rapidly disperse into the atmosphere where it will undergo photochemical degradation.

xylene (1330-20-7)

Ecology - soil

May be harmful to plant growth, blooming and fruit formation.

12.5. Results of PBT and vPvB assessment

64104

vPvB: not relevant – no registration required

12.6. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Dispose of this material and its container to hazardous or special waste collection point.

Additional information : Pressurized container: Do not pierce or burn, even after use.

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

14.1. UN number

UN-No. (ADR) : 1950
UN-No. (IMDG) : 1950
UN-No. (IATA) : 1950
UN-No. (ADN) : 1950
UN-No. (RID) : 1950

14.2. UN proper shipping name

Proper Shipping Name (ADR) : AEROSOLS
Proper Shipping Name (IMDG) : AEROSOLS
Proper Shipping Name (IATA) : Aerosols, flammable
Proper Shipping Name (ADN) : AEROSOLS
Proper Shipping Name (RID) : AEROSOLS
Transport document description (ADR) : UN 1950 AEROSOLS, 2.1, (D)
Transport document description (IMDG) : UN 1950 AEROSOLS, 2.1
Transport document description (IATA) : UN 1950 Aerosols, flammable, 2.1
Transport document description (ADN) : UN 1950 AEROSOLS, 2.1
Transport document description (RID) : UN 1950 AEROSOLS, 2.1

14.3. Transport hazard class(es)

ADR

Transport hazard class(es) (ADR) : 2.1
Danger labels (ADR) : 2.1



IMDG

Racing Black

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Transport hazard class(es) (IMDG) : 2.1
Danger labels (IMDG) : 2.1



IATA

Transport hazard class(es) (IATA) : 2.1
Hazard labels (IATA) : 2.1



ADN

Transport hazard class(es) (ADN) : 2.1
Danger labels (ADN) : 2.1



RID

Transport hazard class(es) (RID) : 2.1
Danger labels (RID) : 2.1



14.4. Packing group

Packing group (ADR) : Not applicable
Packing group (IMDG) : Not applicable
Packing group (IATA) : Not applicable
Packing group (ADN) : Not applicable
Packing group (RID) : Not applicable

14.5. Environmental hazards

Dangerous for the environment : No
Marine pollutant : No
Other information : No supplementary information available

14.6. Special precautions for user

Emergency action in case of accident: : Industrial and institutional users can transport these products as "Limited Quantities" (LQ)

- Overland transport

Classification code (ADR) : 5F
Special provisions (ADR) : 190, 327, 344, 625
Limited quantities (ADR) : 1I
Excepted quantities (ADR) : E0
Packing instructions (ADR) : P207, LP02
Special packing provisions (ADR) : PP87, RR6, L2
Mixed packing provisions (ADR) : MP9

Racing Black

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Transport category (ADR)	: 2
Special provisions for carriage - Packages (ADR)	: V14
Special provisions for carriage - Loading, unloading and handling (ADR)	: CV9, CV12
Special provisions for carriage - Operation (ADR)	: S2
Tunnel restriction code (ADR)	: D

- Transport by sea

Special provisions (IMDG)	: 63, 190, 277, 327, 344, 959
Limited quantities (IMDG)	: SP277
Excepted quantities (IMDG)	: E0
Packing instructions (IMDG)	: P207, LP02
Special packing provisions (IMDG)	: PP87, L2
EmS-No. (Fire)	: F-D
EmS-No. (Spillage)	: S-U
Stowage category (IMDG)	: None

- Air transport

PCA Excepted quantities (IATA)	: E0
PCA Limited quantities (IATA)	: Y203
PCA limited quantity max net quantity (IATA)	: 30kgG
PCA packing instructions (IATA)	: 203
PCA max net quantity (IATA)	: 75kg
CAO packing instructions (IATA)	: 203
CAO max net quantity (IATA)	: 150kg
Special provisions (IATA)	: A145, A167
ERG code (IATA)	: 10L

- Inland waterway transport

Classification code (ADN)	: 5F
Special provisions (ADN)	: 19, 327, 344, 625
Limited quantities (ADN)	: 1 L
Excepted quantities (ADN)	: E0
Equipment required (ADN)	: PP, EX, A
Ventilation (ADN)	: VE01, VE04
Number of blue cones/lights (ADN)	: 1

- Rail transport

Classification code (RID)	: 5F
Special provisions (RID)	: 190, 327, 344, 625
Limited quantities (RID)	: 1L
Excepted quantities (RID)	: E0
Packing instructions (RID)	: P207, LP02
Special packing provisions (RID)	: PP87, RR6, L2
Mixed packing provisions (RID)	: MP9
Transport category (RID)	: 2
Special provisions for carriage – Packages (RID)	: W14
Special provisions for carriage - Loading, unloading and handling (RID)	: CW9, CW12
Colis express (express parcels) (RID)	: CE2
Hazard identification number (RID)	: 23

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Racing Black

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

VOC content : 656 g/l Aerosol products which are used for vehicle refinishing are classed as Annex IIB subcategory (e). The maximum permitted VOC's are 840 g/l. The typical VOC content for this range of products is between 625 and 675 g/l. The VOC regulations do not apply to any other aerosol products except those which are used for vehicle refinishing.

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No

SECTION 16: Other information

Indication of changes:

1.2	Function or use category	Added	
2.2	Precautionary statements (CLP)	Modified	
15.2	Chemical safety assessment	Modified	

Abbreviations and acronyms:

Abbreviations and acronyms: RID: Regulations Concerning the International Transport of Dangerous Goods by Rail ICAO: International Civil Aviation Organization ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonized System of Classification and labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent

Full text of H- and EUH-statements:

Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Asp. Tox. 1	Aspiration hazard, Category 1
Compressed gas	Gases under pressure : Compressed gas
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Gas 1	Flammable gases, Category 1
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT RE 2	Specific target organ toxicity — Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
H220	Extremely flammable gas
H222	Extremely flammable aerosol
H225	Highly flammable liquid and vapour
H226	Flammable liquid and vapour
H229	Pressurised container: May burst if heated
H280	Contains gas under pressure; may explode if heated
H302	Harmful if swallowed
H304	May be fatal if swallowed and enters airways
H312	Harmful in contact with skin
H315	Causes skin irritation
H319	Causes serious eye irritation

Racing Black

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

H332	Harmful if inhaled
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
H373	May cause damage to organs through prolonged or repeated exposure
H411	Toxic to aquatic life with long lasting effects
EUH066	Repeated exposure may cause skin dryness or cracking

SDS EU (REACH Annex II)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product