

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture  
 Article number : 64204  
 Product code : 642

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### 1.2.1. Relevant identified uses

Function or use category : Paint

##### 1.2.2. Uses advised against

No additional information available

#### 1.3. Details of the supplier of the safety data sheet

BARDAHL NL - OCD NEDERLAND BV  
 Maxwellstraat 41  
 3316 GP Dordrecht - Nederland  
 T 0031 78 651 2322 - F 0031 78 617 4848  
[rjonker@bardahl.nl](mailto:rjonker@bardahl.nl) - [www.bardahl.nl](http://www.bardahl.nl)

#### 1.4. Emergency telephone number

Emergency number : +31 (0) 6 2908 2010  
 During office hours: 8.30 t/m 17:00 h

Country	Official advisory body	Address	Emergency number	Comment
Ireland	National Poisons Information Centre Beaumont Hospital	PO Box 1297 Beaumont Road 9 Dublin	+353 1 809 2566 +353 1 809 2166 (public, 8am - 10pm, 7/7)	

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Aerosol, Category 1 H222;H229  
 Serious eye damage/eye irritation, Category 2 H319  
 Specific target organ toxicity — Single exposure, Category 3, Narcosis H336

Full text of H statements : see section 16

##### Adverse physicochemical, human health and environmental effects

Inhalation of fumes or vapours may cause respiratory irritation. May irritate eyes and skin. May cause headache, nausea and irritation of respiratory tract. The preparation is not classified as "dangerous for the environment.". Can form explosive mixture with air. Exposure to fire may cause containers to rupture/explode.

#### 2.2. Label elements

##### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS02

GHS07

Signal word (CLP) : Danger  
 Hazard statements (CLP) : H222 - Extremely flammable aerosol  
 H319 - Causes serious eye irritation  
 H336 - May cause drowsiness or dizziness  
 Precautionary statements (CLP) : P102 - Keep out of reach of children  
 P271 - Use only outdoors or in a well-ventilated area

# 800 Heat Proof Paint

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

P280 - Wear protective gloves, protective clothing, face protection  
P261 - Avoid breathing vapours, spray  
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
P337+P313 - If eye irritation persists: Get medical advice/attention  
P501 - Dispose of contents/container in accordance with local regulations  
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking  
P211 - Do not spray on an open flame or other ignition source  
P251 - Pressurized container: Do not pierce or burn, even after use  
P264 - Wash hands, forearms and face thoroughly after handling  
P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing  
P312 - Call a POISON CENTER or doctor/physician if you feel unwell  
P403+P233 - Store in a well-ventilated place. Keep container tightly closed  
P405 - Store locked up  
P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

EUH-statements : EUH066 - Repeated exposure may cause skin dryness or cracking

### 2.3. Other hazards

vPvB: not relevant – no registration required

## SECTION 3: Composition/information on ingredients

### 3.1. Substance

Not applicable

### 3.2. Mixture

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
acetone, propan-2-one, propanone	(CAS No) 67-64-1 (EC no) 200-662-2 (EC index no) 606-001-00-8 (REACH-no) 01-2119471330-49	30 - 60	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
propane (Note U)	(CAS No) 74-98-6 (EC no) 200-827-9 (REACH-no) 01-2119486944-21	10 - 30	Flam. Gas 1, H220 Compressed gas, H280
xylene (Note C)	(CAS No) 1330-20-7 (EC no) 215-535-7 (EC index no) 601-022-00-9 (REACH-no) 01-2119488216-32	10 - 30	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 STOT RE 2, H373 Asp. Tox. 1, H304
Butane	(CAS No) 106-97-8 (EC no) 203-448-7 (REACH-no) 01-2119474691-32	5 - 10	Flam. Gas 1, H220 Compressed gas, H280
Isobutane	(CAS No) 75-28-5 (EC no) 200-857-2 (REACH-no) 01-2119485395-27	1 - 5	Flam. Gas 1, H220 Compressed gas, H280
2-methylpropan-1-ol, iso-butanol	(CAS No) 78-83-1 (EC no) 201-148-0 (EC index no) 603-108-00-1	< 1	Flam. Liq. 3, H226 STOT SE 3, H335 Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H336
ethylbenzene	(CAS No) 100-41-4 (EC no) 202-849-4 (EC index no) 601-023-00-4 (REACH-no) 01-2119489370-35	< 1	Flam. Liq. 2, H225 Acute Tox. 4 (Inhalation), H332 STOT RE 2, H373 Asp. Tox. 1, H304

Note C : Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.

Note U : When put on the market gases have to be classified as 'Gases under pressure', in one of the groups compressed gas, liquefied gas, refrigerated liquefied gas or dissolved gas. The group depends on the physical state in which the gas is packaged and therefore has to be assigned case by case.

Full text of H-statements: see section 16

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures general : Assure fresh air breathing. Seek medical attention if ill effect develops.

# 800 Heat Proof Paint

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

First-aid measures after inhalation	: Allow breathing of fresh air. If breathing is irregular or stopped, administer artificial respiration. Keep the victim warm. Allow the victim to rest. Obtain emergency medical attention.
First-aid measures after skin contact	: Wash skin thoroughly with mild soap and water. If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after eye contact	: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 15 minutes, holding the eyelids apart. Seek medical attention if irritation develops.
First-aid measures after ingestion	: Do NOT induce vomiting. Drink plenty of water. Never give anything by mouth to an unconscious person. If swallowed, rinse mouth with water (only if the person is conscious). Seek medical attention if ill effect develops.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries after inhalation	: Exposition on high concentrations can cause : May cause headache, nausea and irritation of respiratory tract. This material or its emissions may affect the central nervous system and/or aggravate pre-existing disorders.
Symptoms/injuries after skin contact	: Effects of skin contact may include : redness. Skin irritation.
Symptoms/injuries after eye contact	: Irritating to eyes. Redness, pain.
Symptoms/injuries after ingestion	: Ingestion unlikely.

### 4.3. Indication of any immediate medical attention and special treatment needed

No specific first aid measures are required.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media : Powder. Dry chemical. Sand. Dolomite. Water spray. Water haze.

### 5.2. Special hazards arising from the substance or mixture

Fire hazard : High temperature may liberate toxic gases.  
Explosion hazard : Heating may cause an explosion.

### 5.3. Advice for firefighters

Firefighting instructions : Use water spray or fog for cooling exposed containers.  
Protection during firefighting : Wear suitable protective clothing.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

General measures : Remove ignition sources. No open flames. No smoking. Do not breathe gas, fumes, vapour or spray. Avoid contact with skin and eyes.

#### 6.1.1. For non-emergency personnel

No additional information available

#### 6.1.2. For emergency responders

Protective equipment : Wear proper protective equipment.

### 6.2. Environmental precautions

Not relevant.

### 6.3. Methods and material for containment and cleaning up

Other information : Wear suitable protective clothing. Eliminate every possible source of ignition. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ventilate area. Clear all other personnel from the area.

### 6.4. Reference to other sections

See Heading 8. See Heading 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Additional hazards when processed : Avoid contact with skin and eyes. Do not breathe gas, fumes, vapour or spray.  
Precautions for safe handling : Ensure all national/local regulations are observed. Wear suitable respiratory equipment.

### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Do not expose to temperatures exceeding 50 °C/ 122 °F. Store in dry, cool, well-ventilated area.  
Incompatible materials : heat. sparks. Open flame. Direct sunlight. Moisture.

### 7.3. Specific end use(s)

Aerosolized paint spray.

# 800 Heat Proof Paint

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

acetone, propan-2-one, propanone (67-64-1)		
EU	Local name	Acetone
EU	IOELV TWA (mg/m <sup>3</sup> )	1210 mg/m <sup>3</sup>
EU	IOELV TWA (ppm)	500 ppm
ethylbenzene (100-41-4)		
EU	IOELV TWA (mg/m <sup>3</sup> )	434 mg/m <sup>3</sup>
EU	IOELV TWA (ppm)	100 ppm
EU	IOELV STEL (mg/m <sup>3</sup> )	543 mg/m <sup>3</sup>
EU	IOELV STEL (ppm)	125 ppm
propane (74-98-6)		
EU	IOELV TWA (ppm)	1000 ppm
Netherlands	Suffocating	
xylene (1330-20-7)		
EU	IOELV TWA (mg/m <sup>3</sup> )	435 mg/m <sup>3</sup>
EU	IOELV TWA (ppm)	100 ppm
EU	IOELV STEL (ppm)	150 ppm

#### 8.2. Exposure controls

Personal protective equipment	: Gloves. Protective goggles.
Hand protection	: Safety gloves
Eye protection	: Safety glasses with side guards should be worn to prevent injury from airborne particles and/or other eye contact with this product
Skin and body protection	: Wear suitable protective clothing
Respiratory protection	: In case of insufficient ventilation, wear suitable respiratory equipment. Use protection with appropriate chemical pattern



Other information	: No smoking. Good ventilation of the workplace required. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Do not eat, drink or smoke during use. Remove contaminated clothing immediately.
-------------------	--

### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Aerosol.
Colour	: Black.
Odour	: characteristic.
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: The resin binder in the paint film begins to soften at temperatures in excess of 60 degrees celsius.
Freezing point	: No data available
Boiling point	: The boiling point of the lowest boiling point material is minus 104 degrees celcius (-104). This is the boiling point of the propellant (LPG - Liquefied Petroleum Gas).
Flash point	: The flash point of the lowest flash point material is minus 104 degrees celcius (-104). This is the flash point of the propellant (LPG - Liquefied Petroleum Gas).
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapour pressure	: 590 - 1760 kPa

# 800 Heat Proof Paint

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Relative vapour density at 20 °C	: >1 (Heavier than air)
Relative density	: < 1 Ambient
Solubility	: Insoluble in water.
Log Pow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: 0.8 - 13 vol %

### 9.2. Other information

VOC content	: 652 g/l Aerosol products which are used for vehicle refinishing are classed as Annex IIB subcategory (e). The maximum permitted VOC's are 840 g/l. The typical VOC content for this range of products is between 625 and 675 g/l. The VOC regulations do not apply to any other aerosol products except those which are used for vehicle refinishing.
-------------	---

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

In use may form flammable/explosive vapour-air mixture.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No additional information available

### 10.4. Conditions to avoid

Heat. Open flame. Sources of ignition. Direct sunlight.

### 10.5. Incompatible materials

Strong oxidizers. Strong bases. Strong acids.

### 10.6. Hazardous decomposition products

Carbon dioxide. Carbon monoxide.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity : May cause stomach cramps and vomiting. May cause gastric irritation

<b>acetone, propan-2-one, propanone (67-64-1)</b>	
LD50 oral rat	5800 mg/kg
LD50 dermal rabbit	7800 mg/kg
LC50 inhalation rat (mg/l)	> 20 mg/l/4h
<b>Butane (106-97-8)</b>	
LC50 inhalation rat (mg/l)	658 mg/l/4h
<b>ethylbenzene (100-41-4)</b>	
LD50 oral rat	3500 mg/kg
LD50 dermal rabbit	15415 mg/kg
LC50 inhalation rat (mg/l)	17.8 mg/l/4h
LC50 inhalation rat (ppm)	4000 ppm/4h
<b>Isobutane (75-28-5)</b>	
LC50 inhalation rat (mg/l)	> 50 mg/l/4h
<b>propane (74-98-6)</b>	
LC50 inhalation rat (mg/l)	20 mg/l/4h
<b>xylene (1330-20-7)</b>	
LD50 oral rat	4300 mg/kg
LD50 dermal rabbit	2000 mg/kg
LC50 inhalation rat (mg/l)	6350 mg/l/4h

Skin corrosion/irritation	: Prolonged or repeated contact may cause skin to become dry or cracked. May degrease the skin. Irritating to skin. Eczema
Serious eye damage/irritation	: Irritating to eyes. May cause chemical eye burns
Respiratory or skin sensitisation	: May cause respiratory irritation. Vapours may cause drowsiness and dizziness. Headache
Germ cell mutagenicity	: Not classified

# 800 Heat Proof Paint

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
Specific target organ toxicity (single exposure)	: May cause drowsiness or dizziness.
Specific target organ toxicity (repeated exposure)	: Not classified
Aspiration hazard	: Not classified

### SECTION 12: Ecological information

#### 12.1. Toxicity

<b>acetone, propan-2-one, propanone (67-64-1)</b>	
EC50 Daphnia 1	8800 mg/l
<b>Butane (106-97-8)</b>	
LC50 fish 1	680 mg/l (96h)
<b>ethylbenzene (100-41-4)</b>	
LC50 fish 2	4.2 mg/l
<b>xylene (1330-20-7)</b>	
LC50 other aquatic organisms 1	8.9 - 16.4 mg/l (Pimephales promelas 96h)
EC50 Daphnia 1	3.2 - 9.5 mg/l (Daphnia magna) (48h)

#### 12.2. Persistence and degradability

<b>64204</b>	
Persistence and degradability	This material is expected to be readily biodegradable.
<b>Butane (106-97-8)</b>	
Persistence and degradability	Readily biodegradable.
<b>ethylbenzene (100-41-4)</b>	
Persistence and degradability	Readily biodegradable.
Biochemical oxygen demand (BOD)	1.44 g O <sub>2</sub> /g substance
Chemical oxygen demand (COD)	2.1 g O <sub>2</sub> /g substance
ThOD	3.17 g O <sub>2</sub> /g substance
BOD (% of ThOD)	45.4 % ThOD
<b>Isobutane (75-28-5)</b>	
Persistence and degradability	Readily biodegradable.
<b>propane (74-98-6)</b>	
Persistence and degradability	Readily biodegradable.
<b>xylene (1330-20-7)</b>	
Persistence and degradability	Readily biodegradable.

#### 12.3. Bioaccumulative potential

<b>64204</b>	
Bioaccumulative potential	Bioaccumulation potential.
<b>ethylbenzene (100-41-4)</b>	
BCF fish 1	1
BCF fish 2	15 - 79
BCF other aquatic organisms 1	4.68
Bioconcentration factor (BCF REACH)	< 500
Log Pow	3.15
<b>xylene (1330-20-7)</b>	
BCF fish 2	7 - 26
Bioconcentration factor (BCF REACH)	< 500
Log Pow	3.2

#### 12.4. Mobility in soil

<b>64204</b>	
Ecology - soil	The product contains volatile organic compounds (VOC) which will evaporate easily from all surfaces.

# 800 Heat Proof Paint

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

<b>Butane (106-97-8)</b>	
Ecology - soil	If released into the environment, the product will rapidly disperse into the atmosphere where it will undergo photochemical degradation.
<b>ethylbenzene (100-41-4)</b>	
Surface tension	0.029 N/m
Log Koc	PCKOCWIN v1.66; 2.71; Calculated value; Koc; PCKOCWIN v1.66; 517.8; Calculated value
<b>Isobutane (75-28-5)</b>	
Ecology - soil	If released into the environment, the product will rapidly disperse into the atmosphere where it will undergo photochemical degradation.
<b>propane (74-98-6)</b>	
Ecology - soil	If released into the environment, the product will rapidly disperse into the atmosphere where it will undergo photochemical degradation.
<b>xylene (1330-20-7)</b>	
Ecology - soil	May be harmful to plant growth, blooming and fruit formation.

### 12.5. Results of PBT and vPvB assessment

#### 64204

vPvB: not relevant – no registration required

### 12.6. Other adverse effects

No additional information available

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Dispose of this material and its container to hazardous or special waste collection point.

Additional information : Pressurized container: Do not pierce or burn, even after use.

## SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

### 14.1. UN number

UN-No. (ADR) : 1950  
UN-No. (IMDG) : 1950  
UN-No. (IATA) : 1950  
UN-No. (ADN) : 1950  
UN-No. (RID) : 1950

### 14.2. UN proper shipping name

Proper Shipping Name (ADR) : AEROSOLS  
Proper Shipping Name (IMDG) : AEROSOLS  
Proper Shipping Name (IATA) : Aerosols, flammable  
Proper Shipping Name (ADN) : AEROSOLS  
Proper Shipping Name (RID) : AEROSOLS  
Transport document description (ADR) : UN 1950 AEROSOLS, 2.1, (D)  
Transport document description (IMDG) : UN 1950 AEROSOLS, 2.1  
Transport document description (IATA) : UN 1950 Aerosols, flammable, 2.1  
Transport document description (ADN) : UN 1950 AEROSOLS, 2.1  
Transport document description (RID) : UN 1950 AEROSOLS, 2.1

### 14.3. Transport hazard class(es)

#### ADR

Transport hazard class(es) (ADR) : 2.1  
Danger labels (ADR) : 2.1



#### IMDG

Transport hazard class(es) (IMDG) : 2.1

# 800 Heat Proof Paint

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Danger labels (IMDG) : 2.1



### IATA

Transport hazard class(es) (IATA) : 2.1

Hazard labels (IATA) : 2.1



### ADN

Transport hazard class(es) (ADN) : 2.1

Danger labels (ADN) : 2.1

:

### RID

Transport hazard class(es) (RID) : 2.1

Danger labels (RID) : 2.1

:



#### 14.4. Packing group

Packing group (ADR) : Not applicable

Packing group (IMDG) : Not applicable

Packing group (IATA) : Not applicable

Packing group (ADN) : Not applicable

Packing group (RID) : Not applicable

#### 14.5. Environmental hazards

Dangerous for the environment : No

Marine pollutant : No

Other information : No supplementary information available

#### 14.6. Special precautions for user

Emergency action in case of accident: : Industrial and institutional users can transport these products as "Limited Quantities" (LQ)

#### - Overland transport

Classification code (ADR) : 5F

Special provisions (ADR) : 190, 327, 344, 625

Limited quantities (ADR) : 1I

Excepted quantities (ADR) : E0

Packing instructions (ADR) : P207, LP02

Special packing provisions (ADR) : PP87, RR6, L2

Mixed packing provisions (ADR) : MP9

Transport category (ADR) : 2

Special provisions for carriage - Packages (ADR) : V14

Special provisions for carriage - Loading, unloading and handling (ADR) : CV9, CV12



# 800 Heat Proof Paint

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Special provisions for carriage - Operation (ADR) : S2

Tunnel restriction code (ADR) : D

### - Transport by sea

Special provisions (IMDG) : 63, 190, 277, 327, 344, 959

Limited quantities (IMDG) : SP277

Excepted quantities (IMDG) : E0

Packing instructions (IMDG) : P207, LP02

Special packing provisions (IMDG) : PP87, L2

EmS-No. (Fire) : F-D

EmS-No. (Spillage) : S-U

Stowage category (IMDG) : None

### - Air transport

PCA Excepted quantities (IATA) : E0

PCA Limited quantities (IATA) : Y203

PCA limited quantity max net quantity (IATA) : 30kgG

PCA packing instructions (IATA) : 203

PCA max net quantity (IATA) : 75kg

CAO packing instructions (IATA) : 203

CAO max net quantity (IATA) : 150kg

Special provisions (IATA) : A145, A167

ERG code (IATA) : 10L

### - Inland waterway transport

Classification code (ADN) : 5F

Special provisions (ADN) : 19, 327, 344, 625

Limited quantities (ADN) : 1 L

Excepted quantities (ADN) : E0

Equipment required (ADN) : PP, EX, A

Ventilation (ADN) : VE01, VE04

Number of blue cones/lights (ADN) : 1

### - Rail transport

Classification code (RID) : 5F

Special provisions (RID) : 190, 327, 344, 625

Limited quantities (RID) : 1L

Excepted quantities (RID) : E0

Packing instructions (RID) : P207, LP02

Special packing provisions (RID) : PP87, RR6, L2

Mixed packing provisions (RID) : MP9

Transport category (RID) : 2

Special provisions for carriage – Packages (RID) : W14

Special provisions for carriage - Loading, unloading and handling (RID) : CW9, CW12

Colis express (express parcels) (RID) : CE2

Hazard identification number (RID) : 23

### 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

# 800 Heat Proof Paint

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

VOC content : 652 g/l Aerosol products which are used for vehicle refinishing are classed as Annex IIB subcategory (e). The maximum permitted VOC's are 840 g/l. The typical VOC content for this range of products is between 625 and 675 g/l. The VOC regulations do not apply to any other aerosol products except those which are used for vehicle refinishing.

### 15.1.2. National regulations

No additional information available

### 15.2. Chemical safety assessment

No

## SECTION 16: Other information

Indication of changes:

1.2	Function or use category	Added	
2.2	Precautionary statements (CLP)	Modified	
15.2	Chemical safety assessment	Modified	

Abbreviations and acronyms:

Abbreviations and acronyms: RID: Regulations Concerning the International Transport of Dangerous Goods by Rail ICAO: International Civil Aviation Organization ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonized System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent
---

Full text of H- and EUH-statements:

Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Asp. Tox. 1	Aspiration hazard, Category 1
Compressed gas	Gases under pressure : Compressed gas
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Gas 1	Flammable gases, Category 1
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT RE 2	Specific target organ toxicity — Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
H220	Extremely flammable gas
H222	Extremely flammable aerosol
H225	Highly flammable liquid and vapour
H226	Flammable liquid and vapour
H229	Pressurised container: May burst if heated
H280	Contains gas under pressure; may explode if heated
H304	May be fatal if swallowed and enters airways
H312	Harmful in contact with skin
H315	Causes skin irritation
H318	Causes serious eye damage
H319	Causes serious eye irritation
H332	Harmful if inhaled
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
H373	May cause damage to organs through prolonged or repeated exposure
EUH066	Repeated exposure may cause skin dryness or cracking

# 800 Heat Proof Paint

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

---

SDS EU (REACH Annex II)

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product*